



Electronic Balance

PCCA #35-3241

The Explorer® Pro features an ultra-simple and innovative user interface with on-screen text prompts and scroll down menus. One-step operation guides you through Explorer Pro's application modes with a single button press. The state-of-the-art high-resolution display is easy to view and displays only the information you want to see. Plus, your investment is protected! Explorer Pro is designed with a spill channel and includes an in-use cover.

Limited warranty: 60 months parts and labor.

Standard features include:

- ◆ Simple 2-key menu navigation
- ◆ Text prompts for fast setup
- ◆ 7 application modes plus below balance weighing
- ◆ Brilliant backlit high resolution dot matrix display
- ◆ RS232 port for easy communication
- ◆ GLP compliant with user selectable outputs
- ◆ 5 language operational display text
- ◆ Protective in-use cover and security bracket
- ◆ NTEP-approved

**Ohaus Explorer® Pro Balance —
fully integratable with
PCCA PK SOFTWARE!**



PCCA

compound with confidence®



SPECIFICATIONS

Capacity (g): 410

Readability (g): 0.001

Repeatability (g): 0.0005

Linearity (g): ± 0.002

Weighing Units: gram, milligram, kilogram, pound, ounce, ounce troy, carat, pennyweight, Hong Kong Tael, Singapore Tael, Taiwan Tael, mommes, grain, tical, Newton, custom

Application Modes: weighing, parts counting, animal/dynamic weighing, checkweighing, percent weighing, filling, gross/net/tare weighing

Tare Range: Full capacity by subtraction

Stabilization Time (seconds): 3

Operating Temperature Range: 50° to 86° F / 10° to 30° C

Power Requirements: 100-120 V AC, 220-240 V AC, 50/60 Hz

Calibration: External/Internal

Display Type: High resolution LCD dot matrix with backlight

Pan Size (in/cm): 4.7/12 dia.

Dimensions WxHxD (in/cm): 8.3 x 13.8 x 13.8 / 21 x 35 x 35

Net Weight (lb/kg): 13.2/6